



Fiber Optic Power Reducing Build Out Attenuator, singlemode SC/APC 8°, 10dB, green

- Designed to reduce or balance the power in passive optical networks
- Insertable between the connector and the adapter and therefore suited for distribution frames, cabinets and boxes
- High system flexibility because of wave-length independency and polarization insensitivity

Product Classification

Regional Availability	EMEA Latin America North America
Product Type	Fiber attenuator
Product Series	OCAB

General Specifications

Interface	SC/APC
-----------	--------

Optical Specifications

Fiber Mode	Singlemode
Fiber Type	G.652.D
Attenuation Tolerance	± 10%
Attenuation, nominal	10 dB
Operating Wavelength	1260 – 1360 nm
Optical Power, maximum	250 mW
Return Loss, minimum	55 dB

Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS

UK-ROHS

Compliant/Exempted

Compliant/Exempted

